



Data Sheet

Single/Dual/Quad/Octal TDM-Over-Packet Transport Devices, EEPROM 16kx8 - 2.5V


Manufacturers <u>Microchip Technology</u>, Inc

Package/Case TSSOP-8

Product Type Memory

RoHS Rohs

Lifecycle



Images are for reference only

Please submit RFQ for 24LC128-I/ST or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The Microchip Technology Inc. 24AA128/24LC128/24FC128 (24XX128*) is a 16K x 8 (128 Kbit) SerialElectrically Erasable PROM (EEPROM), capable of operation across a broad voltage range (1.7V to 5.5V). It has been developed for advanced, low-powerapplications such as personal communications or dataacquisition. This device also has a page write capability of up to 64 bytes of data. This device is capable of both random and sequential reads up to the 128Kboundary. Functional address lines allow up to eightdevices on the same bus, for up to 1 Mbit addressspace. This device is available in the standard 8-pinplastic DIP, SOIC (3.90 mm and 5.28 mm), TSSOP, MSOP, DFN, and Chip Scale packages.

Related Products



AT24CM02-SSHM-B

Microchip Technology, Inc SOIC-8



24FC512-I/SM

Microchip Technology, Inc

SOIJ-8



AT24CM02-SSHD-B

Microchip Technology, Inc





24AA512-I/SM

Microchip Technology, Inc SOIJ-8



AT24C512C-SSHM-T
Microchip Technology, Inc
SOIC-8



24LC256-I/ST
Microchip Technology, Inc
TSSOP-8



24LC32AT-I/SN Microchip Technology, Inc SOIC-8



AT24C04D-MAHM-T
Microchip Technology, Inc
UDFN-8