

R5F100LEAFB#30

Data Sheet

MCU 16-bit RL78 CISC 64KB Flash 1.8V/2.5V/3.3V/5V 64-Pin LQFP Tray

Manufacturers Renesas Technology Corp

Package/Case 64-LQFP

Product Type Embedded Processors & Controllers

RoHS

Lifecycle

Please submit RFQ for R5F100LEAFB#30 or Email to us: sales@ovaga.com We will contact you in 12 hours.



Images are for reference only



General Description

Features

CPU: RL78 core, Max. 32MHz

Voltage: 1.6V to 5.5V

Package: 64-pin HTFQFP, 24 to 48-pin HWQFN, 48 to 128-pin LFQFP, 44 to 100-pin LQFP, 20 to 30-pin LSSOP, 64-pin VFBGA, 25 to

36-pin WFLGA

Memory: SRAM Max. 32KB, Program Flash Max. 512KB

Timer: 16-bit Timer (ch) x 8, 8-bit Timer (ch) x 8, Watchdog Timer (ch) x 1, Interval Timer x 1 ch

PWM: PWM Output x 7

Analog function: 10-bit A/D Converter (ch) x 9

On-chip Oscillator Freq. (MHz): High-Speed: 32, 24, 16, 12, 8, 4, 1MHz

Low-speed: 15kHz

Others: RTC, Power-On Reset, Low Voltage Detection

Related Products



R5F21246SNFP

Renesas Technology Corp QFP48



R5F21134FP

Renesas Technology Corp QFP-32



R5S77641N300BG

Renesas Technology Corp BGA



R5F56218BDFP#V0

Renesas Technology Corp 100-LQFP



R5F21368CNFP

Renesas Technology Corp 64-LQFP



R5S77641P300BG

Renesas Technology Corp BGA



R5F562TAADFP#V1

Renesas Technology Corp RX62T32Bit100Mhz



R5F52306ADFM#30

Renesas Technology Corp 64-LQFP