

Transistor Output Optocouplers BV = 2500Vr.m.s. -55C +100C

| | |
|---------------|-----------------------------------------|
| Manufacturers | Renesas Technology Corp |
| Package/Case | SOP4 |
| Product Type | Optocouplers / Photocouplers |
| RoHS | Rohs |
| Lifecycle | |



Images are for reference only

Please submit RFQ for PS2801C-1-V-F3-A or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

Features

High isolation voltage>

Small and thin package (4, 16-pin SSOP, Pin pitch 1.27 mm)

High collector to emitter voltage (V

CEO

Ordering number of tape product: PS2801C-1-F3, PS2801C-4-F3

Pb-Free product

Safety standards UL approved: UL1577, Single protection CSA approved: CAN/CSA-C22.2 No. 62368-1, Basic insulation BSI approved: BS EN 62368-1, Basic/Supplementary insulation (PS2801C-1 only) VDE approved: DIN EN 60747-5-5 (Option)

Related Products




[PS9821-2-F3-AX](#)

Renesas Technology Corp
SOP8



[PS2505L-4-A](#)

Renesas Technology Corp
SSOP-16



[PS7241E-1A-F3-A](#)

Renesas Technology Corp
SOP4



[PS2505L-1-A](#)

Renesas Technology Corp
SOP4



[PS2801C-1-A](#)

Renesas Technology Corp
SSOP-4



[PS2505L-1-F3-A](#)

Renesas Technology Corp
SOP4



[PS2805C-4-F3-A](#)

Renesas Technology Corp
SSOP-16



[PS2501L-1-A](#)

Renesas Technology Corp
DIP-4