



Data Sheet

RFO

Single 16-Channel/Differential 8-Channel, CMOS Analog Multiplexers

Manufacturers Renesas Technology Corp

Package/Case PDIP-28

Product Type Interface ICs

RoHS Rohs

Lifecycle

Please submit RFQ for DG406DJZ or Email to us: sales@ovaga.com We will contact you in 12 hours.

III THINKIN

Images are for reference only

General Description

Maxim's redesigned DG406 and DG407 CMOS analog multiplexers now feature guaranteed matching between channels (8Ω max) and flatness over the specified signal range (9Ω max). These low on-resistance muxes (100Ω max) conduct equally well in either direction and feature guaranteed low charge injection (15pC max). In addition, these new muxes offer low input off-leakage current over temperatureµless than 5nA at $+85^{\circ}C$. The DG406 is a 1 of 16 multiplexer/demultiplexer and the DG407 is a dual 8-channel multiplexer/demultiplexer. Both muxes operate with a +5V to +30V single supply and with $\pm 4.5V$ to $\pm 20V$ dual supplies. ESD protection is guaranteed to be greater than 2000V per Method 3015.7 of MIL-STD 883. These improved muxes are pin-compatible plug-in upgrades for the industry standard DG406 and DG407.

Features	Application
1 0000105	110011011011

ON-Resistance (Max): 100Ω Audio Signal Routing

Low Power Consumption (P_D): <1.2mW Communication Systems

Fast Transition Time (Max): 300ns

Data Acquisition Systems

Low Charge Injection Guidance and Control Systems

TTL, CMOS Compatible Sample-and-Hold Circuits

Single or Split Supply Operation Test Equipment

Pb-Free (RoHS Compliant)

Related Products



DG408DJZ

Renesas Technology Corp

DIP-16



Renesas Technology Corp SOIC-16

DG409DYZ



DG406DYZ

Renesas Technology Corp
SOP-28



DG445DYZ

Renesas Technology Corp
SOIC-16



DG411DYZ
Renesas Technology Corp
SOIC-16



Renesas Technology Corp TSSOP-16

DG408DVZ-T



DG413DYZ-T Renesas Technology Corp SOIC-16

DG412DYZ



Renesas Technology Corp SOIC-16