

IC REG CTRLR BUCK BST PWM 24SSOP

Manufacturers	Analog Devices, Inc
Package/Case	SSOP-24
Product Type	Power Management ICs
RoHS	Pb-free Halide free
Lifecycle	



Images are for reference only

Please submit RFQ for LTC3780EG#TRPBF or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

The LTC3780 is a high performance buck-boost switching regulator controller that operates from input voltages above, below or equal to the output voltage. The constant frequency current mode architecture allows a phase-lockable frequency of up to 400kHz. With a wide 4V to 30V (36V maximum) input and output range and seamless transfers between operating modes, the LTC3780 is ideal for automotive, telecom and battery-powered systems.

The operating mode of the controller is determined through the FCB pin. For boost operation, the FCB mode pin can select among Burst Mode[®] operation, discontinuous mode and forced continuous mode. During buck operation, the FCB mode pin can select among skip-cycle mode, discontinuous mode and forced continuous mode. Burst Mode operation and skip-cycle mode provide high efficiency operation at light loads while forced continuous mode and discontinuous mode operate at a constant frequency.

Fault protection is provided by an output overvoltage comparator and internal foldback current limiting. A power good output pin indicates when the output is within 7.5% of its designed set point.

Features

Single Inductor Architecture Allows VIN Above, Below or Equal to VOUT

Wide VIN Range: 4V to 36V Operation

Synchronous Rectification: Up to 98% Efficiency

Current Mode Control

Phase-Lockable Fixed Frequency: 200kHz to 400kHz

Power Good Output Voltage Monitor

Internal LDO for MOSFET Supply

Quad N-Channel MOSFET Synchronous Drive

VOUT Disconnected from VIN During Shutdown

Adjustable Soft-Start Current Ramping

Foldback Output Current Limiting

Selectable Low Current Modes

Output Overvoltage Protection

Available in 24-Lead SSOP and Exposed Pad (5mm × 5mm) 32-Lead QFN Packages

Application

Automotive Systems

Telecom Systems

DC Power Distribution Systems

High Power Battery-Operated Devices

Industrial Control

Related Products



[LT3763EFE](#)

Analog Devices, Inc
TSSOP28



[LT1038CK](#)

Analog Devices, Inc
TO-3



[LTC4417IUF](#)

Analog Devices, Inc
QFN-24



[LTC3440EMS](#)

Analog Devices, Inc
MSOP10



[LTC1966CMS8#PBF](#)

Analog Devices, Inc
MSOP-8P




[LTC2990IMS#PBF](#)

Analog Devices, Inc
10MSOP



[LTM8045EX#PBF](#)

Analog Devices, Inc
BGA40



[LT4295IUFD#PBF](#)

Analog Devices, Inc
28-WFQFN