

## **MOC3061M**

Data Sheet

Triac & SCR Output Optocouplers 600V Optocoupler Triac Driver ZC

Manufacturers ON Semiconductor, LLC

Package/Case PDIP-6

Product Type Optocouplers / Photocouplers

RoHS Pb-free

Please submit RFQ for MOC3061M or Email to us: sales@ovaga.com We will contact you in 12 hours.



Images are for reference only



## **General Description**

Lifecycle

The MOC306XM and MOC316XM devices consist of a GaAs infrared emitting diode optically coupled to a monolithic silicon detector performing the function of a zero voltage crossing bilateral triac driver. They are designed for use with a triac in the interface of logic systems to equipment powered from 115/240 VAC lines, such as solid-state relays, industrial controls, motors, solenoids and consumer appliances, etc.

**Features** Application

Simplifies Logic Control of 115/240 VAC Power

ONSEMI

Zero Voltage Crossing to Minimize Conducted and Radiated Line Noise

600 V Peak Blocking Voltage

Superior Static dv/dt

600 V/μs (MOC306xM)

1000 V/μs (MOC316xM)

Safety and Regulatory Approvals

UL1577, 4,170 VACRMS for 1 Minute

DIN EN/IEC60747-5-5

Dalated Draduate



**MOC3052M** 

ON Semiconductor, LLC DIP-6



**MOCD213M** 

ON Semiconductor, LLC SOIC-8



**MOC3083SR2M** 

ON Semiconductor, LLC PDIP-6



MOC3023SR2M

ON Semiconductor, LLC PDIP-6



**MOC3022M** 

ON Semiconductor, LLC DIP6



MOC3083SR2VM

ON Semiconductor, LLC PDIP-6



**MOC3043SR2M** 

ON Semiconductor, LLC SOP-6



MOCD223R2M

ON Semiconductor, LLC SOIC-8