

16-Channel Multicell Battery Monitor

Manufacturers	Analog Devices, Inc
Package/Case	80-Lead LQFP (12mm x 12mm w/ EP)
Product Type	Power Management ICs
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for ADBMS6830MWCSWZ or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com). We will contact you in 12 hours.

[RFQ](#)

General Description

The ADBMS6830 is a multicell battery stack monitor that measures up to 16 series connected battery cells with a lifetime total measurement error (TME) of less than 2 mV over the full temperature range. The measurement input range of -2 V to +5.5 V makes the ADBMS6830 suitable for most battery chemistries and allows measurement of voltages across bus bars. Provisions are made for bypassing bus bars without dedicating any measurement channels.

All cells can be measured simultaneously and redundantly with two individual analog-to-digital converters (ADCs). The continuously operating ADCs with a high sampling rate of 4.096 MHz allow reduced external analog filtering and aliasing free measurement results. Higher noise reduction can be achieved by subsequent programmable infinite impulse response (IIR) filters.

Multiple ADBMS6830s can be connected in series, permitting simultaneous cell monitoring of long, high voltage battery strings. Each ADBMS6830 has an isolated serial port interface (isoSPI™) for high speed, RF immune, long distance communications. Multiple devices are connected in a daisy chain with one host processor connection. This daisy chain can be operated bidirectionally, ensuring communication integrity even in the event of a fault along the communication path.

The ADBMS6830 can be powered from the battery stack or an isolated supply. The ADBMS6830 includes passive balancing with individual pulse-width modulation (PWM) duty cycle control and up to 300 mA discharge current for each cell. Other features include an on-board 5 V regulator, up to 10 general-purpose inputs/outputs, and a sleep mode, where current consumption is reduced to 4 µA.

APPLICATIONS

Features

- Measures up to 16 battery cells in series
- Maximum lifetime TME: ±1.8 mV at 3.3 V per cell (-40°C to +125°C)
- Simultaneous and continuous measurement of cell voltages
- Configurable integrated low-pass filtering

Application

- Electric and hybrid electric vehicles
- Backup battery systems
- Grid energy storage

Stackable architecture for high voltage battery packs

Built-in isoSPI interface

2 Mbps isolated serial communications

Uses a single twisted pair, up to 20 meters per segment

Low EMI susceptibility and emissions

Bidirectional for broken wire protection

Capacitor or transformer coupled

2 Mbps isolated serial communications

Uses a single twisted pair, up to 20 meters per segment

Low EMI susceptibility and emissions

Bidirectional for broken wire protection

Capacitor or transformer coupled

Hot plug tolerant without external protection

Passive cell balancing up to 300 mA per channel with programmable pulse-width modulation

Up to 10 general-purpose analog inputs or digital I/O

Temperature or other sensor inputs

Configurable as an I

2

C or SPI master

LPCM for cell and temperature monitoring in key-off state

4 μ A sleep mode supply current

Provisions for bus bars

AEC-Q100 qualified for automotive applications

ADBMS6830WFS models developed for use in ISO 26262 applications for ASIL D

Temperature or other sensor inputs

Configurable as an I

2

C or SPI master

Related Products



[ADP3336ARMZ-REEL7](#)

Analog Devices, Inc
MSOP-8




[ADP3367ARZ](#)

Analog Devices, Inc
SOIC-8



[ADP3330ARTZ3.3-RL7](#)

Analog Devices, Inc
SOT-23-6




[ADR421ARZ](#)

Analog Devices, Inc
SOP-8



[AD737JRZ](#)

Analog Devices, Inc
SOP-8



[AD636JH](#)

Analog Devices, Inc
TO-100-10



[ADR434BRZ](#)

Analog Devices, Inc
SOIC-8



[ADR3412ARJZ-R7](#)

Analog Devices, Inc
SOT-23-6