

ADM3232EARWZ

Data Sheet

RS232 Transceiver RS232, 3V-5.5V supply, 2 Drivers, WSOIC-16

Manufacturers Analog Devices, Inc

Package/Case SOIC-16

Product Type Interface ICs

RoHS Rohs

Lifecycle



Images are for reference only

Please submit RFQ for ADM3232EARWZ or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

All RS-232 (T_OUT and R_IN) and TTL/CMOS (T_IN and R_OUT) inputs and outputs are protected against electrostatic discharges (up to ± 15 kV ESD protection). This ensures compliance with IEC 1000-4-2 requirements.

This device is ideally suited for operation in electrically harsh environments or where RS-232 cables are frequently plugged/ unplugged, with the ± 15 kV ESD protection of the ADM3232E input/output pins.

Emissions are also controlled to within very strict limits. CMOS technology is used to keep the power dissipation to an absolute minimum, allowing maximum battery life in portable applications.

Four external 0.1 µF charge pump capacitors are used for the voltage doubler/inverter, permitting operation from a single 3.3 V supply.

The ADM3232E is available in a 16-lead narrow SOIC package, as well as a space-saving 16-lead TSSOP.

Applications

General-purpose RS-232 data link

Portable instruments

Handsets

Industrial/telecom diagnostic ports

Features

Data rate: 460 kbps

2 Tx and 2 Rx

Meets EIA-232E specifications

 $0.1~\mu F$ charge pump capacitors

ESD protection to IEC1000-4-2 (801.2) on TTL/CMOS and RS-232 I/Os

Contact discharge: $\pm 8~kV$

Air gap discharge: ±15 kV

Application

General-purpose RS-232 data link

Portable instruments

Handsets

Industrial/telecom diagnostic ports



Related Products



ADV7181CBSTZ

Analog Devices, Inc
LQFP-64



AD724JR
Analog Devices, Inc
SOIC-16



ADV7391WBCPZ
Analog Devices, Inc
LFSCP-3



ADV7341BSTZ

Analog Devices, Inc
LQFP-64



Analog Devices, Inc SOP8



ADV7393BCPZ
Analog Devices, Inc
LFCSP-VQ-40



Analog Devices, Inc QFN32



Analog Devices, Inc SOIC-16